



MCA RealSubns®
Q

355nm 266nm

1064nm 532nm

光学参数

(nm)	1064				532				355				266			
(kHz)	1	5	10	20	1	5	10	20	1*	5*	10*	20*	1*	5*	10*	20*
(mW)	120	300	400	400	60	150	150	200	30	50	50	60	10	40	30	40
(J)	120	60	40	20	60	30	15	10	30	10	5	3	10	8	3	2
(ps)	2000		1500		1500	1200		1500	1200		1500	1200				
(8h)	±3%															
	TEM ₀₀															
Typ.(mrad)	@1/e ²	8			6			5			5					
	@1/e ²	8			6			5			5					
	>100:1															

系统参数

	100-240 VAC 50/60 Hz	
	RS232 USB	
(W)	35	
(WxHxL,mm)	168x88x140	
(WxHxL,mm)	45x30x120	
()	15~35	
()	0~60	

波长	型号	重复频率	单脉冲能量
1064	MCA-1064-1-120	1	120
	MCA-1064-5-060	5	60
	MCA-1064-10-040	10	40
	MCA-1064-20-020	20	20
532	MCA-532-1-060	1	60
	MCA-532-5-030	5	30
	MCA-532-10-015	10	15
	MCA-532-20-010	20	10
355	MCA-355-1-030	1	30
	MCA-355-5-010	5	10
	MCA-355-10-005	10	5
	MCA-355-20-003	20	3
266	MCA-266-1-010	1	10
	MCA-266-5-008	5	8
	MCA-266-10-003	10	3
	MCA-266-20-002	20	2

